



HGUIDE N580 INERTIAL/GNSS NAVIGATOR

Honeywell

HGUIDE N580 INERTIAL/GNSS NAVIGATOR

The HGuide n580 is a small, lightweight, self-contained, all-attitude Inertial/GNSS Navigator which can be used for a wide variety of platforms, applications and industries where continuous navigation information is a critical component.



Proven - Dependable - Accurate

The HGuide n580 contains Honeywell's leading edge HG4930 IMU and provides a powerful dual-antenna, multi-frequency, multi-constellation RTK capability. Honeywell's integration expertise blends the IMU and GNSS data to provide an accurate, robust navigation service to your application with all the functionalities that you need.

The HGuide n580 output data includes time stamped position, velocity, angular rate, linear acceleration, roll, pitch and heading information. In dual-antenna mode, the device supports GNSS-based heading measurements and initialization.

KEY HONEYWELL ADVANTAGES

- Honeywell proven navigation algorithms for Air, Land, and Sea
- World class inertial sensor development, calibration, and compensation
- Proven reliability, dependability, and ruggedness
- Accepts RTCM3 GNSS corrections
- Highest performing Inertial/GNSS navigator of its size, weight, and price
- Configuration flexibility. Only purchase the features you need.
- Multiple configurable communication ports
- The HGuide n580 is not ITAR controlled. Its Export Control Classification Number (ECCN) is 7A994.

HGUIDE n580 TYPICAL KEY CHARACTERISTICS

GNSS Capability (Varies by Configuration)	SBAS, Post-Processed Kinematic (PPK), and RTK mode options Single or Dual Antenna capable
GNSS Signals (Varies by Configuration)	GPS L1 C/A, L1C, L2C, L2P, L5; GLONASS L1 C/A, L2 C/A, L2P, L3, L5; BeiDou B1, B2; Galileo E1, E5 AltBOC, E5a, E5b; NavIC (IRNSS) L5; SBAS L1, L5 QZSS L1 C/A, L1C, L2C, L5; L-Band up to 5 channels
Supply Voltage/Power Consumption	+9VDC to +36VDC / 7 Watts (Varies by Configuration)
Weight/Volume	495g (1.1 lbs) / 324 cm ³ (19.8 in ³), ~9 cm x 6cm x 6cm
Operating Temperature Range	-40°C to +71°C
Compliance	IP68, FCC, ISED, CE, RoHS, WEEE
Communication Ports	Navigation Interface, RS-422 and 5 VDC CMOS (Configurable) RCM3 Correction - RS422 and RS232 (Configurable)
Discrete Signals	PPS 5V CMOS Output (Supports Lidar Integration)

For More Information

aerospace.honeywell.com/HGuide

Honeywell Aerospace

2600 Ridgway Parkway
Minneapolis MN 55413
aerospace.honeywell.com

N61-1863-000-001 | 12/19
© 2019 Honeywell International Inc.

**THE
FUTURE
IS
WHAT
WE
MAKE IT**

Honeywell